

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
27 December 2002 (27.12.2002)

PCT

(10) International Publication Number
WO 02/103393 A2

- (51) International Patent Classification⁷: **G01V**
- (21) International Application Number: **PCT/US02/18225**
- (22) International Filing Date: **10 June 2002 (10.06.2002)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data:
09/882,952 **15 June 2001 (15.06.2001)** **US**
- (71) Applicant: **WESTERNGECO, L.L.C. [US/US]; 10001 Richmond Avenue, Houston, TX 77042 (US).**
- (72) Inventor: **ZAJAC, Mark; 20530 Autumn Terrace Lane, Katy, TX 77450 (US).**
- (74) Agents: **FIGATNER, David, S. et al.; WesternGeco Intellectual Property Department, 10001 Richmond Avenue, Houston, TX 77042 (US).**

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *without international search report and to be republished upon receipt of that report*

[Continued on next page]

(54) Title: **ACTIVE SEPARATION TRACKING AND POSITIONING SYSTEM FOR TOWED SEISMIC ARRAYS**



(57) Abstract: A method and apparatus comprising an active control system for a towed seismic streamer array that enables any relative positional control of any number of towed seismic streamers. The streamer positions are controlled horizontally and vertically using active control units positioned within the seismic array. The three component (x,y,z) position of each streamer element, relative to the vessel and relative to each other is controlled, tracked and stored during a seismic data acquisition run. The active control elements can be located at diverter position, streamer head, along the length of the streamer or on the tail of the streamer. The apparatus and method of the present invention enables a seismic array to be maneuvered as the towing vessel maintains course or the vessel itself maneuvers to assist in the repositioning of the array. The system enables maintenance of specific array position and geometry in the presence of variable environmental factors. The present invention facilitates four-dimensional seismic data acquisition by sensing and storing the position of the array and each array element with respect to time. Ancillary configurations such as collapsing an array or one section one streamer of an array for maintenance, handling or retrieval are enabled.

WO 02/103393 A2